Penteco BGM ES1

- Containment
- Erosion Control
- Leak Detection
- Water Proofing
- Protection

Penteco's ES1 is an elastomeric modified bituminous geomembrane. It is manufactured by impregnating a polyester geotextile fiberglass layer with an elastomeric compound. The geotextile provides the mechanical resistance and a high puncture resistance. The elastomeric bitumen provides the waterproofing properties of the geomembrane and ensures its longevity.

The installation of this geomembrane can be allowed in low temperatures down to -40°C, ideal for Canadian winters. The high friction angle of bitumen of 34 degrees for example provides a strong adherence in steep slopes, allowing a high volume of material placement directly on the geomembrane.

BGM - ES1				
Property		Test Method	Imperial	Metric
Thickness	Average	ASTM D-5199	137.8 mil	3.50 mm
	Minimum		122 mil	3.10 mm
Surface Mass	Average	- ASTM D-5261	123.9 oz/yd²	4.20 kg/m²
	Minimum		109.1 oz/yd²	3.70 kg/m²
Tear Resistance (average)	Longitudinal Direction	- ASTM D-4073	169 lbf	750 N
	Cross Direction		112 lbf	500 N
Strength (average)	Longitudinal Direction	ASTM D-7275	126 lbf/in	22 KN/m
	Cross Direction		103 lbf/in	18 KN/m
Elongation (average)	Longitudinal Direction	ASTM D-7275	60%	60%
	Cross Direction		60%	60%
Flexibility at Low Temperature (average)	Longitudinal Direction	- ASTM D-5147	-4°F	-20°C
	Cross Direction		-4°F	-20°C
Puncture Resistance	Average	ASTM D-4833	101 lbf	450 N
Water Permeability	Average	ASTM E-96	7 x 10 ⁻¹⁴ m/s	
Gas Permeability	Average	ASTM D-1434-82	3 x 10 ⁻⁴ m³/(m².d.atm)	
Dimensions				
Typical Roll Size		Measured	16.7 ft x 320 ft	5.10 m x 100 m
Area		Calculated	5344 ft²	510 m²

Notes:

- (1) Roll Widths/ Lengths vary based on manufacturer.
- (2) All roll widths/lengths have a tolerance of ±1 %.
- (3) Custom roll lengths can be ordered. Transportation cost might be affected.
- (4) Penteco is a distributor for this product.
- (5) Manufacturer's data sheet provided at time of purchase.

Distributed by

